

# AXL 2



This versatile bulkhead is an ideal utility emergency luminaire for internal or external use.



## Features

- Non-maintained or maintained
- High temperature long life batteries
- Polycarbonate oversized housing
- 3 Hour emergency duration
- Zero maintenance with led lifespan of 30,000 hours(L 70)
- Manufactured to BS 60598-2-22
- Self-adhesive legends included
- Wireless Control System Available
- IP65 / IK08 Rated


## Applications

-  Custodial
-  Education
-  Food-Processing
-  Health Care
-  Industry
-  Leisure
-  Manufacturing
-  Office
-  Retail
-  Social Housing
-  Warehouse

## Accessories

- AX/SRB** Recessing Bezel

## Dimensions



# AXL 2



## Technical Details

Part No.	Description	Power (W)	Luminaire Lumens	LI/cW
AXL2-M3	Emergency Bulkhead   350mm	2.5	250	100

Body Material	Diffuser Material	Housing Colour	Mounting Type	CCT Offering	CRI	SDCM	UGR Rating	Dimmable	Dimming Method
Polycarbonate	Polycarbonate	RAL9003	Surface	4K	80+	3 step Macadam Ellipse	N/A	Available	SwitchDIM/DALI

IP Rating	IK Rating	Operating Temperature (°C)	L/B value <sup>*A</sup>	Terminal Information	Warranty	Weight (kg)
IP65	IK08	-20° + 40°	60K+ L90/B10	2.5mm Push connector	5 Year warranty 1 year parts and Labour Inclusive	

<sup>\*A</sup>: L/B value based on Ta25°C operating temperature, standard operation of luminaire within stated parameters. For specific detail please contact [info@powerlitefitz.co.uk](mailto:info@powerlitefitz.co.uk)

Please contact [info@powerlitefitz.co.uk](mailto:info@powerlitefitz.co.uk) for the Inrush current (A) & No. Per 10A breaker.