

IP65 Impact

A versatile IP65 rated lowbay luminaire suitable for a wide range of installations. A fully welded, raw stainless steel body provides an IP65 Finish.



Features

- Frosted LED diffuser
- Supplied with Eyebolts for simple hanging installation
- Fully welded stainless steel housing
- Pre-wired with 1M PVC flex via M20 cable gland
- 22K, 27K, 3K, 4K, 5K, 65K LEDs

Applications

- Car Park
- Food Processing
- Industry
- Manufacturing
- Warehouse


Options and Accessories

- EML** EM LiFePO4 (4W)
- EMLST** EM Selftest LiFePO4 (4W)
- CF** Corridor Function
- DD** SwitchDIM/DALI
- WL** Wireless Control System
- WLEM** Wireless Monitored Emergency
- PIR** Programmable PIR
- BKT** Surface/Trunking Mounting Bracket
- WH** White Colour Option

Technical Details

Part No.	Description	Power (W)	Luminaire Lumens	LI/cW
IMPACT-IP-72-4K	IP65 Stainless Steel Lowbay Fitting	72	8730	121.3
IMPACT-IP-108-4K	IP65 Stainless Steel Lowbay Fitting	108	13,070	121.0
IMPACT-IP-144-4K	IP65 Stainless Steel Lowbay Fitting	144	17,500	121.5
IMPACT-IP-180-4K	IP65 Stainless Steel Lowbay Fitting	180	22,200	123.3
IMPACT-IP-210-4K	IP65 Stainless Steel Lowbay Fitting	210	26,278	125.1

Photometric



Dimensions

