

Regor 1

The Regor LED 1 is a wall mounted IP65 wallpack with an opal diffuser and conduit entry.



Features

- Conduit entry to top and sides
- Polycarbonate construction
- Opal diffuser
- Integral sensors option
- Photocell option
- New slimline design
- IK08
- IP65
- Removable eyelid feature
- Wireless Control System Available
- 22K, 27K, 3K, 4K, 5K, 65K LED Options


Applications

- Car Park
- Warehouse
- External


Options and Accessories

- EMFL** EM LiFePO4 (4W)
- EMFLST** EM SELFTTEST LiFePO4 (4W)
- EMFLP** EM PRO LiFePO4 (4W)
- PC** Photocell
- MW** On/Off HF Sensor (IR Programmer required)

Photometric



Dimensions



Regor 1



Technical Details

Part No.	Description	Power (W)	Luminaire Lumens	LI/cW
R1L-SL-8-30-4K	Multi Wattage Slimline Wall Pack	8 - 30	907 - 3100	113.4

Additional Information

Body Material	Diffuser Material	Housing Colour	Mounting Type	CCT Offering	CRI	SDCM	UGR Rating	Dimmable	Dimming Method
Polycarbonate	Polycarbonate	RAL9004	Surface	22K, 27K, 3K, 4K, 5K, 65K	80+	3 step Macadam Ellipse	N/A	N/A	N/A

IP Rating	IK Rating	Operating Temperature (°C)	L/B value ^A	Inrush current (A) ^B	No.Per 10A breaker ^C	Terminal Information	Warranty	Weight (kg)
IP65	IK08	-20° + 40°	60K+ L90/B10	15W - 8A 48µs 30W - 8A 48µs	15W - 55 30W - 55	2.5mm Push connector	5 Year warranty 1 year parts and Labour Inclusive	1.84

Example Code

Standard Part No.	Description	Addon Suffix	Suffix Description
R1L-SL-8-30-4K	Multi Wattage Slimline Wall Pack	MW	On/Off HF Sensor (IR Programmer required)
		EMFL	EM LiFePO4 (4W)

Final Part No.	Description
R1L-SL-8-30-MW-EMFL-4K	Multi Wattage Slimline Wall Pack On/Off HF Sensor (IR Programmer required) EM LiFePO4 (4W) 4000K

^A: L/B value based on Ta25°C operating temperature, standard operation of luminaire within stated parameters. For specific detail please contact info@powerlitefz.co.uk

^B: This applies only to our standard product offering.

^C: This applies only to our standard product offering.