

Urban Round

A die-cast aluminium IP65 LED fitting. It features side conduit entries and has an eyelid option.



Features

- Die-cast aluminium base
- Side and top conduit entries
- Security screw option
- Integral sensor options
- IP65 & IK10
- 22K, 27K, 3K, 4K, 5K, 65K LEDs

Applications

- Car Park
- External
- Industry
- Social Housing
- Vandal Resistant


Options and Accessories

- EM Integral Emergency
- EMST Integral Emergency Self Test
- PC Photocell
- CF Corridor Function
- MWP Remote Programmable Microwave
- DD SwitchDIM/DALI
- WL Wireless Control System
- WLEM Wireless Emergency Monitoring
- EL Eyelid Attachment
- BK Black finish

Technical Details

Part No.	Description	Power (W)	Luminaire Lumens	LI/cW
URR-10-4K	Die-cast Aluminium Circular Bulkhead White Body	10	1226	122.6
URR-14-4K	Die-cast Aluminium Circular Bulkhead White Body	14	1662	118.7
URR-21-4K	Die-cast Aluminium Circular Bulkhead White Body	21	2431	115.8
URR-10-BK-4K	Die-cast Aluminium Circular Bulkhead Black Body	10	1226	122.6
URR-14-BK-4K	Die-cast Aluminium Circular Bulkhead Black Body	14	1662	118.7
URR-21-BK-4K	Die-cast Aluminium Circular Bulkhead Black Body	21	2431	115.8

Photometric



Dimensions

