

# Pitstar

An IP69K sealed luminaire for harsh environments. The end caps are fabricated from 304 stainless steel or aluminium. The housing is either polycarbonate or acrylic depending on agent exposure. It is IK10 rated for all versions and features flexible mounting options.



### Features

- IP69k
- IK10+
- Adjustable bracket mounts in stainless steel
- Stainless steel or aluminium end caps
- Dimmable
- Directional light
- 22K, 27K, 3K, 4K, 5K, 65K LEDs

### Applications

- External
- Food Processing
- Hazardous
- Industry
- Manufacturing
- Roadways
- Vandal Resistant


### Options and Accessories

- CLT** Clear Tube
  - DD** DALI/switchDIM
  - EM** Integral emergency
  - 27K** 2700K
  - 3K** 3000K
  - 5K** 5000K
  - 65k** 6500K
- Available in Red, Blue, Green, Yellow or Amber LED Colour

### Technical Details

Part No.	Description	Power (W)	Luminaire Lumens	LI/cW
PIT-32-IP69K-4K	PIT light   1070mm	32	4480	140.0
PIT-50-IP69K-4K	PIT light   1270mm	50	7000	140.0
PIT-68-IP69K-4K	PIT light   1570mm	68	9384	138.0

### Photometric



### Dimensions

