

Hurricane

The Hurricane is the perfect UK solution for exterior environments that require a modern, durable, cost-effective bulkhead. The Hurricane comes with side and top conduit entries, allowing for flexible installation methods.



Features

- Polycarbonate body
- Side and top conduit entries
- IP65 rated
- Security screw option
- Integral sensor options
- No visible screws
- Snap on bezel
- White & black finish available
- 22K, 27K, 3K, 4K, 5K, 65K LED Options


Applications

-  Education
-  Social-Housing
-  Architectural
-  External

Accessories

- | | |
|---------------|---|
| EMFL | EM LiFePO4 (4W) |
| EMFLST | EM SELFTEST LiFePO4 (4W) |
| EMFLP | EM PRO LiFePO4 (4W) |
| MW | On/Off HF Sensor (IR Programmer required) |
| CF | Corridor Function |
| DD | SwitchDIM/DALI |

Dimensions



Hurricane



Technical Details

Part No.	Description	Power (W)	Luminaire Lumens	LI/cW
HUR-10-21-BK-4K	Multi Wattage Black Circular Body	10 - 21	1200 - 2520	120.0
HUR-10-21-WH-4K	Multi Wattage White Circular Body	10 - 21	1200 - 2520	120.0

Body Material	Diffuser Material	Housing Colour	Mounting Type	CCT Offering	CRI	SDCM	UGR Rating	Dimmable	Dimming Method
Polycarbonate	Polycarbonate	RAL9005	Surface Conduit	22K, 27K, 3K, 4K, 5K, 65K	80+	3 step Macadam Ellipse	N/A	Available	SwitchDIM/DALI

IP Rating	IK Rating	Operating Temperature (°C)	L/B value ^A	Terminal Information	Warranty	Weight (kg)
IP65	IK10	-20° + 40°	60K+ L90/B10	2.5mm Push connector	5 Year warranty 1 year parts and Labour Inclusive	1.0

*A: L/B value based on Ta25°C operating temperature, standard operation of luminaire within stated parameters. For specific detail please contact info@powerlitefitz.co.uk
Please contact info@powerlitefitz.co.uk for the Inrush current (A) & No.Per 10A breaker.